1060 Aluminum Sheet

1060 Aluminum Sheet h14 Aluminum Sheet Metal Description:

Mingtai Aluminum focuses on the R&D and production of hot-rolled 1060 aluminum sheets. 1060 aluminum sheets have high elongation, tensile strength, excellent electrical conductivity, and high formability, and can meet conventional processing requirements (stamping, stretching). Mingtai Aluminum's ultra-wide and ultra-thick 1060 aluminum plate can eliminate internal stress and cut without deformation. The width can reach 2650mm and the thickness can reach 500mm. It is a rare domestic manufacturer that can produce ultra-wide and ultra-thick aluminum plates.

Strength of Mingtai Aluminum Production 1060 Aluminum Sheet

- 1. 1060 alloy aluminum plate has good forming processing characteristics, high corrosion resistance, good weldability and electrical conductivity.
- 2. The technology is mature, and the price of 1060 aluminum sheet has a huge advantage compared with other high-grade alloy aluminum sheets;
- 3. Possess an internationally advanced "1+4" hot rolling production line with an ultra-high production capacity of 450,000 tons;
- 4. The product has a flat shape, precise geometric dimensions, high surface gloss, and good alkali cleaning effect, which can reach A-level in the water brushing test
- 5. Mingtai 1060 aluminum alloy plate supports customization, and there are patterned aluminum plate, embossed aluminum plate, and non-slip aluminum plate for your choice.

Technical Parameter of Henan Mingtai 1060 Aluminum Sheet

Alloy	1060			
Temper	O,H12,H14,H16,H18,H19,H22,H24 , H26,H28,			
	H112			
Thickness (mm)	0.1-500			
Width (mm)	20-2650			
Length (mm)	500-16000			

Countries we have exported our products to:

Aluminium 1060 Sheet Exporters:					
Nepal	Turkeu	Italy	Alregia	India	
South Korea	France	UAE	Poland	Pakistan	

Aluminum products of Mingtai Aluminum meet the export popular

- 1) Standard seaworthy export packaging. Wooden pallets with plastics protection for the coil and sheet.
- 2) The packaging can be eye to sky or eye to wall based on the customer's requirement
- 3) 16-20 MT can be located into 20FCL, the sea freight rate is much cheaper than 40FCL. Delivery Time: 15-35 days after receiving LC or deposit 30%