

## 5182 Aluminum Sheet

### Experienced Manufacturer 5182 Aluminum Sheet

The 5182 aluminum is Al-Mg-Si alloy, with widely usage, especially in the construction industry and automotive industry , Good corrosion resistance, good weld-ability, good cold work-ability and medium strength. The main elements of 5182 is Mg, and also with a small amount of Si, so the welding of 5182 aluminum sheet used in gas welding, argon arc welding, spot welding and seam welding performance are good.

### Strength of Mingtai Aluminum Production 5182 Aluminum Sheet

1. 2,000 Tons/Month output, high production capability will shorten your wait time.
2. Mingtai Aluminum has strong strength, with 6 semi-continuous casting production lines, 10 continuous casting and rolling production lines, and 44 other large-scale processing equipment, with an annual production capacity of 140,000 tons
3. Advanced equipment. The introduction of SMS six-roll cold rolling mill equipment can produce 2600mm ultra-wide 5182 aluminum.
4. Factory Direct Sale. All of the products are directly ex-factory prices, which greatly reduces the cost of intermediate circulation, so the price is much more advantageous in the market.

### Technical Parameter of Mingtai 5182 Aluminum Sheet

Alloy	5182
Temper	F,O,H12,H14,H16 H18,H19,H22,H24, H26,H28,H111,H112,H114
Thickness (mm)	0.4-500
Width (mm)	100-2650
Length (mm)	500-16000

### Countries we have exported our products to:

For more than 20+ years, Henan Mingtai Aluminum has been supplying high-quality 5182 aluminum sheets. Because of this, it has become one of the leading 5182 aluminum sheet manufacturers in China. Our aluminum sheets 5182 are welcomed in the market:

Aluminium 5086 Sheet Exporters:				
Saudi Arabia	Oman	Kuwait	Netherlands	Pakistan
Bahrain	Qatar	UAE	Africa	China
Nigeria	Mexico	Canada	Venezuela	United Kingdom
United States	South Africa	Malaysia	Bangladesh	Turkey
Singapore	Sri Lanka	Australia	Brazil	Germany
France	Italy	South Korea	Poland	Belgium

### How to Pack and ship the Aluminum Sheet 5182?

- 1) Standard seaworthy export packaging. Wooden pallets with plastics protection for the coil and sheet.
- 2) The packaging can be eye to sky or eye to wall based on the customer's requirement
- 3) 16-20 MT can be located into 20FCL, the sea freight rate is much cheaper than 40FCL.

Delivery Time: 15-35 days after receiving LC or deposit 30%